

Understanding Automation and Vessel-Control Systems


An owner's guide to processors, logic, networks, fallback and recovery

Automation can reduce workload, but it can also hide shared dependencies.

Readiness depends on knowing what happens when the control system is no longer available.

Absolute Marine

Commercial thinking for private cruising.



SENSE | DECIDE | ACT

GUIDE OVERVIEW

What automation and vessel-control systems are designed to do

Automation systems coordinate sensors, logic, operator commands and actuators so machinery and hotel systems operate in the correct sequence. Their purpose is to reduce workload without removing control or awareness.

SCOPE

This guide covers common PLC, distributed control and integrated vessel-management arrangements on cruising yachts. It provides owner-level understanding rather than software-design or commissioning instructions. Current vessel drawings, logic descriptions and manufacturer documentation remain the primary references.

By the end of this guide, you should be able to:

- Trace a command from sensor or operator input through logic, network, output module and working equipment.
- Distinguish automatic, manual, local, remote, maintenance and emergency operating modes.
- Recognise configuration faults, failed inputs or outputs, network loss, processor restart and hidden common dependencies.
- Understand the difference between an alarm, an interlock, a permissive, a trip and a manual override.
- Ask better questions during purchase, survey, refit, software change and offshore preparation.

CORE PRINCIPLE

Automation should make safe operation easier, not make the yacht impossible to operate when one processor, screen, network or power supply fails.


Safety

Control systems may start motors, move valves, transfer fuel, change electrical sources or shut down machinery automatically. Isolate hazardous energy and use approved test procedures before simulating inputs, forcing outputs, bypassing interlocks or placing equipment in manual mode.

SYSTEM ARCHITECTURE

How sensing, logic and actuation fit together

A complete control path includes a physical condition, input device, processor or controller, logic, output module, actuator, feedback and operator interface. Any layer can fail or misrepresent the true state.




Layer	What it contributes	Owner focus
Sensors and operator inputs	Provide process values, positions, selections and commands.	Plausibility, location, fail state and independent verification.
Control processors / PLCs	Execute the stored logic and communicate with remote modules and interfaces.	Power, health indication, program version, spare hardware and restart behaviour.
Input/output modules	Convert field wiring into controller signals and controller commands into field action.	Channel labels, spare capacity, environmental condition and replaceability.
Networks and gateways	Move data and commands between distributed equipment.	Topology, power, termination, configuration and what remains if a link is lost.
Actuators and working equipment	Move valves, start pumps, change source or alter machinery output.	Actual movement, local position, manual operation and safe fail position.
HMI and event history	Present status, allow commands and record sequence.	Clear modes, priorities, user permissions, clock and configuration backup.

FEEDBACK CLOSES THE LOOP	A command shown as accepted is not proof that the pump started, valve moved or breaker closed. Reliable control uses suitable feedback from the equipment.
--------------------------	--

PROCESSORS AND I/O

PLCs, controllers, remote modules and field wiring

Control processors rarely fail in isolation. Power supplies, memory, communications, firmware, input modules, output relays and field wiring all determine whether the programmed logic reaches the real equipment.



A healthy processor indicator does not prove every input and output channel is healthy.

Area	Common weakness	Owner focus
Processor and memory	Restart loop, memory corruption, ageing storage, unsupported firmware or failed real-time clock.	Status indicators, diagnostics, program backup, battery where fitted and supplier support.
Controller power supply	Voltage dip, overheated PSU, loose terminal or one common supply removes several controllers.	Input source, output voltage, alarm on failure, redundancy and cooling.
Digital inputs	Broken wire, reversed normal state, contact bounce or moisture creates false status.	Fail-safe logic, end-of-line monitoring where used and physical comparison.
Analogue inputs	Wrong scaling, lost loop power, noise, shared reference or frozen value.	Signal type, range, engineering units, quality flag and independent measurement.
Digital outputs	Stuck relay, failed transistor, welded contactor or output command without equipment response.	Output indication, feedback contact and manual means of stopping equipment.
Remote I/O cabinet	Water, heat, vibration, network loss or one module affects many local systems.	Enclosure condition, network/power redundancy, spare module and channel map.


**DO NOT FORCE
OUTPUTS CASUALLY**

Forcing an output can bypass normal interlocks, create unexpected movement and remain active after testing. Use controlled specialist procedures and record every temporary override.

SENSORS, ACTUATORS AND FEEDBACK

The difference between a command and the real physical state

Automation depends on trustworthy inputs and actuators that can reach the required position. Local mechanical, hydraulic or electrical faults may appear to the controller as a logic problem.



Useful feedback should be sufficiently independent of the command path to reveal a failed actuator or wrong position.

Component	Possible failure	Owner focus
Limit / position switch	Misalignment, failed contact, loose target or indication changes before the mechanism is safe.	Confirm physical travel, not only the screen symbol.
Motorised valve / damper	Actuator stalls, coupling slips, local handwheel left engaged or valve seizes.	Command, current, travel time, local indicator and manual operation.
Pump / fan starter	Output relay energises but breaker, contactor, overload or motor fails.	Run feedback, current/flow/pressure response and local stop.
Variable-frequency drive	Network command, local mode, fault code, cooling or parameter change prevents intended speed.	Local/remote state, reference source, bypass and stored parameter backup.
Hydraulic / pneumatic actuator	Low pressure, leakage, air loss or manual valve position defeats the electrical command.	Energy source, isolation, pressure and safe fail position.
Sensor disagreement	Multiple sensors diverge or one plausible reading is wrong.	Use logic that detects disagreement and preserve a local independent check.


OBSERVE THE PROCESS RESPONSE

If a cooling pump is commanded on, confirm pressure or flow changes. If a transfer valve moves, confirm the correct tank trend. Feedback should reflect the task, not only the relay.

HUMAN-MACHINE INTERFACES

Screens, commands, permissions and mode awareness

The HMI should help the crew understand what the yacht is doing and why. A sophisticated display is a liability if operating mode, command authority or failure state is unclear.



The interface should distinguish commanded, permitted, active, failed and manually overridden states.

Area	Common weakness	Owner focus
Mode indication	Auto, manual, local, remote or maintenance mode is unclear or hidden on another page.	Persistent visible mode and authority at every control station.
Command confirmation	Touch command is accepted with no clear feedback or can be triggered accidentally.	Confirmation for high-consequence actions and positive result indication.
User permissions	Shared passwords, unknown administrator access or crew can change engineering settings.	Role-based access, current accounts, secure recovery method and change log.
Touchscreen / display failure	One screen is the only route to pumps, valves, alarms or source selection.	Alternative station, physical controls, spare display and configuration image.
Screen design	Dense graphics, inconsistent colours or hidden alarm detail slows response.	Simple hierarchy, readable labels and consistent symbols across systems.
Remote app or tablet	Wireless, account, software or battery failure removes control or creates unauthorised access.	Supplement only; maintain secure onboard local control.

KNOW WHO HAS CONTROL

A local/remote selector, bridge command station or automatic sequence can reject another command. The crew should recognise authority transfer before assuming the equipment has failed.

DATA NETWORKS AND INTEGRATION

CAN, Modbus, Ethernet and proprietary control links

Integrated systems exchange values, commands and statuses through networks and gateways. One failed switch, power supply, terminator or software configuration can affect many unrelated functions.



Area	Failure or change risk	Owner focus
CAN / fieldbus	Termination, voltage, connector corrosion, duplicate address or one noisy node disrupts communication.	Topology, terminators, power feeds, fault-isolation method and spare connectors.
Serial / Modbus	Address, baud rate, parity, register map or polarity does not match replacement equipment.	Configuration record and known lost-communication behaviour.
Ethernet switch	Single switch, water ingress, loop, IP conflict or unsupported hardware removes several systems.	Power redundancy, configuration backup, spare switch and documented ports.
Gateway / protocol converter	One device becomes the only path between otherwise independent systems.	Local fallback, spare hardware, licence and configuration file.
Remote access	Internet service, account compromise or vendor connection changes the system without onboard awareness.	Controlled access, logs, updates, MFA where supported and ability to disable safely.
Software compatibility	New display, PLC or engine software breaks an older interface or changes data meaning.	Compatibility matrix, staged update and full functional test after change.

NETWORK LOSS NEEDS A DEFINED STATE	Equipment should fail to a safe or predictable mode, and the crew should be told which controls and indications remain local when communication is lost.
------------------------------------	--

MODES, PERMISSIVES AND INTERLOCKS

Why the system accepts, rejects or stops a command

Automatic control normally checks conditions before starting equipment and may stop it when a protective condition is reached. The crew should understand the difference between a command being rejected and equipment failing to respond.



The reason for an unavailable command should be visible without forcing or guessing.

Feature	Example	Owner focus
Start permissive	Cooling available, valve open, breaker healthy or tank level adequate before a pump or generator starts.	Identify which permissive is missing and whether the indication is true.
Mutual interlock	Two incompatible valves, sources or pumps cannot be selected together.	Do not defeat without understanding the physical consequence.
Protective trip	Low oil pressure, high temperature, overspeed or electrical fault stops equipment.	Preserve event evidence and correct the cause before reset.
Mode-dependent logic	Alarm, delay or sequence changes between harbour, passage, unattended or maintenance modes.	Mode should be visible and automatically return where appropriate.
Maintenance inhibit	An alarm or automatic action is suppressed to permit work.	Register, reason, owner, expiry and independent restoration check.
Emergency override	Allows limited operation despite a failed sensor or controller.	Use only the documented method, with added watch and reduced limits.


A REJECTED COMMAND CAN BE CORRECT BEHAVIOUR

Before assuming a controller fault, check whether the system is protecting against a closed valve, low level, unavailable cooling source or conflicting mode.

AUTOMATIC SEQUENCES

Timers, state machines and recovery after interruption

Many yacht functions are sequences rather than single commands: generator start, source transfer, fuel transfer, bilge response, stabiliser deployment and shutdown all require steps in the correct order.




Sequence issue	What can happen	Owner focus
Step timeout	The system waits for feedback that never arrives and stops the sequence.	Identify the missing physical action, not only the timeout alarm.
Skipped or repeated step	Software, input bounce or restart causes unexpected valve or breaker action.	Event log, software version and controlled test of the complete sequence.
Power interruption mid-sequence	Equipment remains in an intermediate position while the controller restarts.	Known restart state, safe mechanical position and resumption procedure.
Simultaneous automatic demands	Several pumps, compressors or generators start together and overload power or fluid capacity.	Priority, staggering, load shedding and maximum simultaneous demand.
Manual intervention during auto sequence	Crew command conflicts with logic or leaves the system between modes.	Clear transfer of authority and procedure for abandoning the sequence.
Failed return to normal	Temporary bypass, local mode or fault latch remains after recovery.	Post-event checklist and independent confirmation of normal mode.

RECOVERY IS PART OF THE DESIGN	The control system should have a predictable state after power loss, network interruption or emergency stop. Restarting everything automatically is not always the safest answer.
--------------------------------	---

POWER SUPPLIES AND REDUNDANCY

Keeping control available during the fault it must manage

Automation may be required during blackout, fire, flooding or machinery failure. Its processors, networks, interfaces and actuators should not all depend on the same normal power source.



Redundancy must include power, communications, hardware, software and the physical equipment being controlled.

Area	Hidden shared dependency	Owner focus
Dual controllers	Both share one cabinet, power supply, network switch, software database or environmental fault.	Physical and functional independence, switchover test and spare program.
UPS / backup battery	Aged cells, failed charger or low capacity supports screens but not remote I/O or actuators.	Endurance test with the complete control chain operating.
Essential DC converters	One converter supplies PLC, network, HMI and field instruments.	Alarm on loss, spare unit and what transfers automatically.
Network redundancy	Two network paths share one power source, cable route or gateway.	Controlled failover and clear indication of degraded mode.
Manual fallback	Local controls still require the failed PLC output, network or electrically operated valve.	Trace the fallback path to the physical equipment.
Environmental control	Both control cabinets depend on one fan, air-conditioning unit or leak-prone location.	Temperature, water ingress, ventilation and separation.

TEST THE DEGRADED STATE

Normal operation with every controller and network healthy does not show whether the yacht can preserve steering, bilge, fuel, cooling or electrical control after one control-system failure.

MANUAL FALLBACK AND LOCAL CONTROL

Operating safely when automation is degraded

Manual fallback should be deliberate, labelled and usable in the conditions where it may be needed. It is not simply a hidden switch that bypasses the controller.




Fallback type	What it should provide	Owner focus
Local motor starter	Direct start/stop independent of central command, where safe.	Local overload, run feedback, remote inhibit and risk of automatic restart.
Manual valve / handwheel	Physical positioning after actuator or controller failure.	Accessibility, actual position, locking and re-engagement of actuator.
Hard-wired emergency control	Dedicated command path for a critical pump, shutdown or source transfer.	Independent power and clear boundary between normal and emergency use.
Standalone local panel	Continues operating the subsystem without the vessel network.	Local alarms, modes, set points and ability to rejoin central control.
Software manual mode	Allows direct output command through the same PLC/HMI.	Not a true fallback if the processor, screen or network is the failed element.
Temporary watchkeeping control	Manual rounds and local gauges compensate for lost automation.	Defined frequency, limits, crew endurance and escalation point.

RECONCILE BEFORE RETURNING TO AUTO	The physical valve, breaker, pump and controller memory may disagree after manual operation. Confirm the actual state before automation regains authority.
------------------------------------	--

FAILURE AWARENESS

Common weaknesses and immediate response

Control-system failures may look like equipment faults, and equipment faults may look like logic faults. Use independent indications and preserve event evidence before repeated resets.



The displayed symptom may be several layers away from the initiating fault.

Evidence or failure	Possible cause	Immediate thinking
Several unrelated systems fail together	Shared PLC, network switch, power supply, remote-I/O cabinet or common software service.	Look for the shared layer before treating every subsystem separately.
Screen responds but equipment does not	Output, field wiring, starter, actuator, permissive or local mode prevents action.	Verify command, output and physical feedback step by step.
Equipment operates unexpectedly	Automatic sequence, stale command, software error, failed input or unintended local/remote transfer.	Protect people, stop safely and preserve event/configuration evidence.
Repeated controller restart	Power dip, overheating, memory fault, network storm or software crash.	Avoid endless cycling; preserve essential control and investigate supply/environment.
Value freezes or jumps	Sensor, scaling, network quality or display database fault.	Use local physical indication and treat the safest credible condition.
Manual fallback fails	Fallback still depends on failed power/network, selector seized or procedure not understood.	Reduce the operating plan and escalate before critical options disappear.


DO NOT NORMALISE IT

A touchscreen that often needs rebooting, a valve that occasionally reports the wrong position or a system that must be left in manual after every start is an unresolved reliability defect.

SOFTWARE, CHANGE AND CYBER RESILIENCE

Keeping configuration controlled and recoverable

Automation is partly physical equipment and partly stored information. A successful replacement or update requires the correct program, parameters, licences, passwords and commissioning evidence.



A backup is only valuable when it can be identified, restored to compatible hardware and verified.

Area	Risk	Owner focus
Program and configuration backup	File is missing, unlabelled, password-protected or older than later modifications.	Offline copies, version/date, hardware identity and restore test where practical.
Software update	Changes communication, timing, alarm behaviour or compatibility with old devices.	Release notes, rollback plan, staged testing and no casual update before departure.
Passwords and licences	Former contractor or owner retains access while current crew cannot administer the system.	Current credentials, secure recovery, licence ownership and vendor contacts.
Remote service connection	Unauthorised or accidental changes occur through VPN, cloud or modem access.	Access approval, logs, MFA where supported and ability to disable remotely managed links.
Removable media / laptops	Malware, wrong project file or unlicensed software affects the controller.	Controlled engineering devices, backups and supplier procedure.
Obsolescence	Processor, HMI, operating system or proprietary network is unsupported.	Migration plan, spare hardware and preservation of source files before failure.


DO NOT UPDATE FOR CONVENIENCE ALONE

A working but older system may be more reliable than a poorly tested replacement. Balance security, supportability and operational risk with a controlled migration plan.

TESTING AND MAINTENANCE STRATEGY

Proving normal, fault and fallback behaviour

Maintenance should confirm not only that individual components work, but that the complete control sequence behaves correctly after power loss, network failure, manual intervention and restoration.



Area	Good maintenance evidence	Why it matters
Processors and I/O	Diagnostics, temperatures, power quality, module status and spare hardware recorded.	Finds ageing hardware and common supply problems before complete loss.
Sensors and actuators	Calibration or functional test includes physical movement and independent feedback.	Prevents the controller reporting a safe state that does not exist.
Networks and gateways	Topology, terminations, traffic health, power feeds and configuration backups verified.	Supports fault isolation and replacement of shared infrastructure.
Interlocks and sequences	Permissives, timeouts, trips, restart and fallback tested under approved scenarios.	Proves the yacht behaves correctly outside normal operation.
HMI and event history	Modes, permissions, commands, clocks, alarms and logs remain accurate.	Supports crew decisions and post-event diagnosis.
Change records	Every program, parameter, hardware and network change has reason, version and test result.	Prevents undocumented modifications becoming hidden failure causes.

Useful spares, records and tools

- Compatible controller, I/O, power-supply, relay, network-switch or HMI spares where replacement is realistic.
- Current program and configuration backups, licences, passwords and restore instructions.
- Network diagrams, point lists, interlock descriptions, mode tables and manual-fallback procedures.
- Selected sensors, switches, connectors and field relays for critical functions.
- Specialist vendor and local integrator contacts, including support for obsolete hardware.

WORK TO REFER	PLC programming, safety interlock changes, control-cabinet live work, propulsion or steering control, fire-system integration and commissioning of automatic sequences require competent specialists.
---------------	---

OFFSHORE READINESS

Buyer questions and readiness checklist

An offshore-ready automation system is documented, supported and tested, with clear control authority, resilient power and networks, usable local fallback and recoverable configuration.

Area	Questions for purchase or survey
Architecture	Can processors, I/O, networks, gateways, HMIs, power supplies, actuators and fallback paths be traced on current drawings?
Software and support	Are program backups, versions, passwords, licences, supplier access and compatible spare hardware available?
Operating modes	Are auto, manual, local, remote, maintenance and emergency modes clear and understood?
Interlocks and sequences	Do permissives, trips, timeouts, restart states and source-transfer sequences have current functional tests?
Networks and power	What remains after loss of one controller, network switch, gateway, UPS, DC converter or central display?
Manual fallback	Can critical pumps, valves, sources and shutdowns be operated locally without the failed control layer?
History and risk	Are recurring reboots, false positions, undocumented changes, failed updates or obsolescence fully explained?

Quick readiness check

	Readiness statement
☐	I can trace critical commands from input through logic, output, actuator and feedback.
☐	Control modes and command authority are clearly shown at every relevant station.
☐	Current programs, configurations, licences, passwords and drawings are backed up and accessible.
☐	There are no unexplained processor resets, network faults, false positions or recurring manual overrides.
☐	Critical controllers, networks and interfaces remain available after a realistic power-source failure.
☐	Interlocks, automatic sequences and restart behaviour have been tested under controlled procedures.
☐	Local or manual fallback reaches the physical equipment without relying on the failed control layer.
☐	More than one person knows how to stabilise the yacht and transfer to degraded control.

KEY TAKEAWAY

Dependable automation combines trustworthy inputs, controlled logic, verified outputs, resilient power and networks, clear operating modes, recoverable configuration and manual fallback that the crew can actually use.

Guidance to consult

Use current vessel control-system drawings, logic descriptions, point lists and the installed PLC, HMI, network, drive, actuator and machinery manufacturers' instructions, together with applicable flag-state, coding, class, insurance and yard requirements.

Understanding Yacht Systems

Practical guides for owners, buyers
and offshore cruising crews.

AMTG-027

Understanding Automation and Vessel-Control Systems

RELATED GUIDES

AMTG-003 Understanding Marine Electrical Systems

AMTG-004 Understanding Electrical Redundancy

AMTG-023 Understanding AC and DC Distribution

AMTG-025 Understanding Load Shedding and Blackout Recovery

AMTG-026 Understanding Monitoring and Alarm Systems

AMTG-032 Understanding Emergency Shutdown Systems

ABOUT ABSOLUTE MARINE

Independent technical advice for explorer yacht owners,
buyers and offshore cruising yacht owners.

Survey Report Reviews | Offshore Readiness Reviews
Reliability | Risk | Readiness

absolute-marine.co.uk

info@absolute-marine.co.uk